EXPLORER 710

High-Speed, Portable BGAN Terminal



Product Sheet



EXPLORER 710

High-Speed, Portable BGAN Terminal

Raising the BGAN bar

EXPLORER 710 is a portable satellite terminal set to usher in a new era in the world of BGAN by setting new standards for size, speed and features.

Smallest and Lightest

The smallest full Class 1 BGAN terminal positioned to support broadcasters by enhancing the quality of mobile outside broadcasting.



Specifications

Dimensions		
Total H / W / D:		332 / 279 / 54 mm
		13.07 / 10.98 / 2.13 inches
Total weight:		3.5 kg / 7.7 lbs (incl. battery)
Antenna:		1.9 kg / 4.2 lbs
Transceiver (incl. b	attery):	1.6 kg / 3.5 lbs
Global Services		
Voice:		4 kbps AMBE+2
Premium voice:		3.1 kHz audio, 64 kbps
Standard IP:		Up to 492 kbps
Streaming IP:		32, 64, 128 kbps
		(256 kbps & BGAN X-Stream)
HDR Streaming:		Min. 600 kbps
		Min. 300 kbps (Half-channel
HDR)		
ISDN:		UDI 64 kbps / RDI 56 kbps
SMS:		Not supported
Inmarsat frequencies:		1518.0 - 1525.0 MHz (Rx) (EMEA
		1525.0 - 1559.0 MHz (Rx)
		1626.5 - 1660.5 MHz (Tx)
		1668.0 - 1675.0 MHz (Tx) (EMEA
EIRP:		20dBW ±1dB
User Interface:	PMOLED Display, 5 navigation keys, Audio and LCD pointing aids and LED indicator, Compass	
Languages:	UK, FR, DE, ES, RU and CN	
		t Class 1 Type Approval at launch C at launch. Other approvals TBC

Fastest ever BGAN

The first and only BGAN terminal to support the full High Data Rate on-demand streaming service from Inmarsat. With speeds averaging 650 kbps, the EXPLORER 710 sets a new standard for mobile video newsgathering.

Double the speed with Plug & Play bonding; simply connect two EXPLORER 710 terminals with an ethernet cable and achieve streaming rates over 1 Mbps.

Interfaces

1 x Analogue RJ-11 phone/	/fax interfaces
2 x LAN (RJ-45) interface	
Power over Ethernet:	PoE Cl. 2 on one RJ-45 interface
Max. cable length:	100m / 328ft (Cat5 UTP)
1 x USB host interface	
2.0 (host), Charging up t	io 2A
1 x ISDN interface	
Connector type:	RJ-45
Max. units per port:	8, max. total power supplied 1W
1 x Transceiver / Antenna i	nterface
Connector type:	TNC-TNC
Max. cable loss:	1.4 / 20dB @ 1.5GHz
1 x BGAN SIM-Card slots	
WLAN Access Point	

Standard: IEEE 802.11 b/g

Environmental conditions

Temperature	
Operational (ambient):	-25°C to +55°C / -13°F to +131°F
Storage (excl. battery):	-40°C to +80°C / -40°F to +176°F
Battery storage temperature	2
1 month:	-20°C to +60°C / -4°F to +140°F
3 months:	-20°C to +45°C / -4°F to +113°F
1 year:	-20°C to +20°C / -4°F to +68°F
Water and dust:	Transceiver: IP52 / Antenna: IP66
Relative humidity:	95% non-condensing
	at +40°C / +104°F

Power

Receive time, max .:

DC input range:	10-32VDC
Power consumption Intelligent Power Managem	ent 65W (max.)
AC/DC power supply	
Input:	100-240VAC, 47-63Hz, 65W
Output:	19VDC
Connector type:	2.5 / 5.5 mm power jack
Battery:	Lithium ion, rechargeable
Stand-by time:	36 hours
Transmit time, max.:	2h30m @ 144 kbps
(25°C / 77°F)	1h30m @ 650 kbps

3h30m @ 492 kbps



Smart and Easy

EXPLORER 710 introduces smart devices to the world of BGAN, enabling users to connect their own smart phone for terminal control, voice calls and connectivity. The EXPLORER Connect App with a SIP softphone is available on Android and IOS.

Other features include a USB host interface, hot-swappable batteries, a large easy-to-use LED display and multiple interfaces to support a wide range of applications.

Other features

Built-in SIP server Embedded Webserver		
Advanced Router with admin control		
Wireless Access Point		
Battery hot-swap and Built-in BGAN bonding		
Remote activation and remote management		
EXPLORER Connect App for IOS and Android:		
Includes a SIP Softphone, Terminal Access to control your		
BGAN and Pointing Assistance.		
EXPLORER Cellular Modem for USB:		
With the EXPLORER LTE Modem you can connect local cellular		
networks and use the EXPLORER 510 as wireless router for all		
your devices.		

Package

EXPLORER 710 Transceiver & Antenna incl. rechargeable lithium ion battery, Antenna cable, 2m ISDN/LAN cable, 115/230VAC power supply, Quick start guide.

Accessories

	5501165	
40372	0B-100	EXPLORER 710 Antenna
40368	6G	Lithium Ion Battery
40372	0B-010	Battery Hot Swap Cable
40368	2P	100-240V AC/DC Power Supply
40365	0A-009	Car Charger Cable
40367	0A-00500	IP Handset incl. Cradle
40365	0A-921	Pole Mount Kit
40372	0B-942	10m Antenna Cable
40372	0B-945	30m Antenna Cable
40372	0B-947	50m Antenna Cable
40372	0B-953	80m Antenna Cable
40375	6A-0500	EXPLORER Cellular USB Modem

Product number

403720B-00500

EXPLORER 710 Terminal